江苏斯尔邦石化有限公司
JiangSu Sierbang Petrochemical Co.,Ltd.
Tel:886-0518-81391500
Fax:0518-81393070
Website:www.shenghongpec.com
Email:evaxiaoshou@shenghongpec.com
PC:222065
地址：江苏省连云港市徐圩新区港前大道
Address:Gangqian Road,Xuwei New Area,Lianyungang City,Jiangshu Province,China

斯尔邦石化 SIERBANG PETROCHEMICAL

EVA

特性 Characterics

UE28400为乙烯-醋酸乙烯酯共聚物，由Basell釜式法工艺生产，具有高流动性，粘附性优异，耐低温性良好，相容性良好。

UE28400 is an ethylene-vinyl acetate copolymer (EVA), produced by Autoclave process licensed by Basell. It offers high flowability ,excellent adhesion, good low temperature resistance and compatibility.

应用 Applications

热熔胶 hot melt adhesives

性能 Properties

项　目 Properties	单位 Unit	典型值 Typical Value	测试方法 Test Method
VA 含量 VA contents	wt.%	28	GB/T 30925
熔融指数 Melt Index	g/10min	410	Sierbang method
拉伸断裂强度 Tensile Strength at Break	MPa	2.0	GB/T 1040
拉伸断裂伸长率 Elongation at Break	%	420	GB/T 1040
维卡软化温度 Vicat Softening Point	℃	28	GB/T 1633
熔点 Melt Point	℃	63	GB/T 19466

上述指标为实验室典型数据，斯尔邦石化公司保证以上数据真实准确，仅用于应用参考，不应该以此作为标准规格。使用上述信息，所发生的一切责任概与本公司无关，所有风险应由用户自行承担。

The data listed here is intended to provide typical values and to recommend product applications, should not be used to establish specification limits. Users are responsible for determine whether our product and data are suitable for their particular purpose and for the compliance with related law. The data contained herein is true and accurate. However, since conditions of use are beyond our control, SAILBOAT Petrochemical assumes no obligation or liability for the data in this document.